

EVINRUDE® E-TEC®

60 HP

SPECIFICATIONS

Engine Type	Inline 2-Cylinder E-TEC D.I.
Bore x Stroke - in (mm)	3.62 x 2.60 (92 x 66)
Displacement - cu in (cc)	53 (864)
Gear Ratio	2.9:1
Full Throttle RPM Range	5500-6000 RPM
Starting	Electric
Controls	Mechanical / Tiller
Fuel Induction	E-TEC Direct Injection with Stratified Low RPM Combustion Mode
Alternator Output - Amps*	81 Total / 25 @ Wide Open Throttle
Trim Method	Power Trim & Tilt
Trim Range	-4° to 16°
Tilt Range	65°
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - qt (L)	2 (1.9)
Recommended Oil	XPS Marine XD100 / XD50
Recommended Fuel	87 Octane
Warranty	5-Year Non-Declining**
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union



COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - lb (kg)
Graphite	20 (508)	Remote (Tiller acc.)	E60DPGL	240 (109)
	20 (508)	Tiller	E60DGTL	250 (113)
White	20 (508)	Remote (Tiller acc.)	E60DSL	240 (109)

* Variable Voltage Computer Controlled 81 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 25 Amp.

** 3 years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T.

Specifications subject to change.

©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

