

EVINRUDE® E-TEC®

150 HP

SPECIFICATIONS

Engine Type	V6 60° E-TEC D.I.
Bore x Stroke - in (mm)	3.62 x 2.60 (92 x 66)
Displacement - cu in (L)	158.2 (2.6)
Full Throttle RPM Range	5400-6000 RPM
Starting	Electric
Controls	Mechanical
Fuel Induction	E-TEC Direct Injection with Stratified Low RPM Combustion Mode
Alternator Output - Amps*	133 Total / 50 @ Wide Open Throttle
Steering	Remote
Trim Method	Power Trim and Tilt
Trim Range	-6° to 15°
Tilt Range	75°
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - gal (L)	Accessory 1.8 (6.8) 3 (11.3) & 10 (37.85) Tank Available
Recommended Oil	XPS Marine XD100 / XD50
Recommended Fuel	87 Octane
Warranty	5-Year Non-Declining**
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union



INSTALLATION	COLOR	SHAFT LENGTH - in. (mm)	MODEL NO.	WEIGHT - lb (kg)	GEAR RATIO
Single	Graphite	20 (508)	E150DGL	418 (190)	1.85:1
		25 (635)	E150DGX	433 (196)	1.85:1
	White	20 (508)	E150DSL	418 (190)	1.86:1
Single+ / Multiple	White	25 (635)	E150DPX†	433 (196)	1.85:1
			E150DCX‡	433 (196)	

* Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

** 3 years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T.

† Standard Rotation model available for single and multiple installation.

‡ Corresponding Counter Rotation model.

Specifications subject to change.

©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

