

# EVINRUDE® E-TEC® G2®

# 250 HP

## SPECIFICATIONS

Engine Type	V6 74° E-TEC G2 D.I.
Bore x Stroke - in (mm)	3.85 x 3.00 (98 x 76)
Displacement - cu in (L)	210 (3.4L)
Gear Ratio	1.85:1
Full Throttle RPM Range	5400-6000 RPM
Starting	Electric
Controls	ICON II Digital Shift and Throttle
Fuel Induction	E-TEC Direct Injection with Stratified Low RPM Combustion Mode
Alternator Output - Amps*	133 Total / 50 @ Wide Open Throttle / 14 @ Idle
Trim Method	Power Trim & Tilt
Trim Range	-6° to 15°
Tilt Range	81°
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - gal (L)	On-Engine 2 (7.5) / Accessory 1.8 (6.8), 3 (11.3) & 10 (37.85)
Recommended Oil	XPS Marine XD100
Recommended Fuel	87 Octane
Warranty	5-Year Non-Declining** / 5-Year Corrosion
Mounting Centers - in (mm)	Minimum 28 (711)
Engine Color	Slate Gray or Classic White
Color Customization	Unlimited
Integrated Features	Dual Axis Rigging / iTrim
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union



INSTALLATION	COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - lb (kg)
Single† / Multiple	Slate Gray	25 (635)	iSteer DPS	H250GXF†	569 (258)
			IHS / Tiebar	H250GXC‡	558 (253)
		25 (635)	iSteer DPS	H250WXF†	569 (258)
			IHS / Tiebar	H250WXC‡	558 (253)
	Classic White	25 (635)	Optimus 360 / IHS	H250WXI	558 (253)
			IHS / Tiebar	H250WXC‡	558 (253)
		30 (762)	iSteer DPS	H250WZF†	569 (258)
			IHS / Tiebar	H250WZC‡	570 (259)
			Optimus 360 / IHS	H250WZI	570 (259)
			IHS / Tiebar	H250WZC‡	570 (259)

\* Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

\*\* 3 years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T.

† Standard Rotation iSteer DPS model available for single and multiple installation. All iDOCK and Optimus 360 models available for multiple installation only.

‡ Corresponding Counter Rotation model.

Specifications subject to change.

©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

