

EVINRUDE® E-TEC®

# 25 HP

## SPECIFICATIONS



Engine Type	Inline 2-Cylinder E-TEC D.I.
Bore x Stroke - in (mm)	2.992 x 2.5 (76 x 64)
Displacement - cu in (cc)	35 (575)
Gear Ratio	2.15:1
Full Throttle RPM Range	5500-6000 RPM
Controls	Mechanical / Tiller
Fuel Induction	E-TEC Direct Injection with Stratified Low RPM Combustion Mode
Alternator Output - Amps*	56 Total / 15 @ Wide Open Throttle
Trim Range	-4° to 16°
Tilt Range	65°
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - qt (L)	1.7 (1.6)
Recommended Oil	XPS Marine XD100 / XD50
Recommended Fuel	87 Octane
Warranty	5-Year Non-Declining**
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union

COLOR	SHAFT LENGTH - in. (mm)	STEERING	STARTING	TRIM METHOD	MODEL NO.	WEIGHT - lb (kg)	
Graphite	15 (381)	Tiller (Remote avail.)	Rope (Electric acc.)	Manual Tilt	E25DRG	150 (68)	
			Electric & Rope	Manual Tilt	E25DGTE	162 (74)	
			Rope (Electric acc.)	Manual Tilt	E25DRGL	154 (70)	
	20 (508)	Tiller (Remote avail.)	Manual Tilt	E25GTEL	166 (75)		
			Electric & Rope	Power Trim & Tilt	E25DGTL	187 (85)	
			Remote (Tiller avail.)	Electric & Rope	Power Trim & Tilt	E25DPGL	181 (82)
White	15 (381)	Tiller (Remote avail.)	Rope (Electric acc.)	Manual Tilt	E25DRS	150 (68)	
			Rope (Electric acc.)	Manual Tilt	E25DRSL	154 (70)	
	20 (508)	Tiller (Remote avail.)	Electric & Rope	Power Trim & Tilt	E25DTSL	187 (85)	
			Remote (Tiller avail.)	Electric & Rope	Power Trim & Tilt	E25DPSL	181 (82)

\* Variable Voltage Computer Controlled 56 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 15 Amp.  
 \*\* 3 years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T.

Specifications subject to change.

©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

