

EVINRUDE® E-TEC®

90 HP

SPECIFICATIONS

| | |
|---------------------------------|--|
| Engine Type | Inline 3-Cylinder E-TEC D.I. |
| Bore x Stroke - in (mm) | 3.62 x 2.60 (92 x 66) |
| Displacement - cu in (L) | 79 (1.29) |
| Gear Ratio | 2.00:1 |
| Full Throttle RPM Range | 5000-5500 RPM |
| Starting | Electric |
| Controls | Mechanical |
| Fuel Induction | E-TEC Direct Injection with Stratified Low RPM Combustion Mode |
| Alternator Output - Amps* | 81 Total / 25 @ Wide Open Throttle |
| Steering | Remote (Tiller accessory) |
| Trim Method | Trac-1 Power Trim and Tilt |
| Trim Range | -4° to 17° |
| Tilt Range | 75° |
| Lubrication | Multi-Point Targeted Oiling |
| Oil Tank Capacity - qt (L) | 3 (2.8) |
| Recommended Oil | XPS Marine XD100 / XD50 |
| Recommended Fuel | 87 Octane |
| Warranty | 5-Year Non-Declining** |
| 100% Global Emissions Compliant | EPA 2013 / CARB 3 STAR / European Union |



| COLOR | SHAFT LENGTH - in. (mm) | MODEL NO. | WEIGHT - lb (kg) | GEAR RATIO |
|----------|-------------------------|-----------|------------------|------------|
| Graphite | 20 (508) | E90DPGL | 320 (145) | 2.36:1 |
| | 25 (635) | E90DGX | 335 (152) | 2.25:1 |
| White | 20 (508) | E90DSL | 320 (145) | 2.36:1 |
| | 25 (635) | E90DPX | 335 (152) | 2.25:1 |

* Variable Voltage Computer Controlled 81 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 25 Amp.

** 3 years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T. Specifications subject to change.

©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, ™ and the BRP logo are trademarks of BRP or its affiliates.

