

EVINRUDE® PORTABLES

9.8 HP

SPECIFICATIONS

Engine Type	2-cylinder
Bore x Stroke - in (mm)	2.17 x 1.73 (55 x 44)
Displacement - cu in (cc)	12.8 (210)
Gear Ratio	2.08:1
Full Throttle RPM Range	5000-6000 RPM
Fuel Induction	Carbureted
Oil Tank Capacity - fl oz (ml)	27 (800)
Recommended Oil	Evinrude/ Johnson 5W40 Ultra 4-Stroke Oil
Recommended Fuel	87 Octane
Warranty	3-Year, Non-Declining
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union



COLOR	SHAFT LENGTH - in. (mm)	STEERING	CONTROLS	STARTING	TRIM METHOD	ALTERNATOR OUTPUT	MODEL NO.	WEIGHT - lb (kg)
Graphite	15 (381)	Tiller	Tiller Handle	Rope	Manual	N/A	E10RG4	81.5 (37)
		Tiller	Tiller Handle	Rope	Manual	N/A	E10RGL4	84 (38)
	20 (508)	Tiller	Tiller Handle	Electric	Power Tilt	12V, 145W, 6A	E10TPL4	102.5 (46)
		Remote	Mechanical	Electric	Power Tilt	12V, 145W, 6A	E10PGL4	103.6 (47)

