

EVINRUDE® E-TEC®

# 30 HP

## SPECIFICATIONS



Engine Type	Inline 2-Cylinder E-TEC D.I.
Bore x Stroke - in (mm)	2.992 x 2.5 (76 x 64)
Displacement - cu in (cc)	35 (575)
Gear Ratio	2.15:1
Full Throttle RPM Range	5500-6000 RPM
Controls	Mechanical / Tiller
Fuel Induction	E-TEC Direct Injection with Stratified Low RPM Combustion Mode
Alternator Output - Amps*	56 Total / 15 @ Wide Open Throttle
Trim Range	-4° to 16°
Tilt Range	65°
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - qt (L)	1.7 (1.6)
Recommended Oil	XPS Marine XD100 / XD50
Recommended Fuel	87 Octane
Warranty	5-Year Non-Declining**
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union

COLOR	SHAFT LENGTH - in. (mm)	STEERING	STARTING	TRIM METHOD	MODEL NO.	WEIGHT - lb (kg)
Graphite	15 (381)	Tiller (Remote avail.)	Rope (Electric acc.)	Manual Tilt	E30DRG	150 (68)
			Rope (Electric acc.)	Manual Tilt	E30DRGL	154 (70)
	20 (508)	Tiller (Remote avail.)	Electric & Rope	Manual Tilt	E30GTEL	166 (75)
				Power Trim & Tilt	E30DGTL	187 (85)
			Remote (Tiller avail.)	Electric & Rope	Power Trim & Tilt	E30DPGL
White	15 (381)	Tiller (Remote avail.)	Rope (Electric acc.)	Manual Tilt	E30DRS	150 (68)
			Rope (Electric acc.)	Manual Tilt	E30DRSL	154 (70)
	20 (508)	Tiller (Remote avail.)	Electric & Rope	Power Trim & Tilt	E30DTSL	187 (85)
				Power Trim & Tilt	E30DPSL	181 (82)

\* Variable Voltage Computer Controlled 56 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 15 Amp.

\*\* 3 years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T.

Specifications subject to change.

©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

